

## FW-175 LOW NOISE TYPE COOLING TOWER SPECIFICATION

<b>Manufacturer</b>	<b>RYOWO (HOLDING) CO., LTD.</b>
<b>Type</b>	<b>Induced Draft Cross Flow Vertical Discharge Type</b>
<b>Origin</b>	<b>China</b>

<table border="1"> <tr> <td><b>1 Design Condition</b></td> <td></td> </tr> <tr> <td>Nominal Flow (m<sup>3</sup>/hr)</td> <td>175.0</td> </tr> <tr> <td>Water Out Temp.</td> <td>32°C</td> </tr> <tr> <td>Water In Temp.</td> <td>37°C</td> </tr> <tr> <td>Ambient Wet Bulb Temp.</td> <td>28°C</td> </tr> <tr> <td colspan="2"><b>2 Overall Dimension</b></td> </tr> <tr> <td>Length (mm)</td> <td>4400</td> </tr> <tr> <td>Width (mm)</td> <td>2300</td> </tr> <tr> <td>Height (mm)</td> <td>4430</td> </tr> <tr> <td>Net Weight (kgs)</td> <td>1525</td> </tr> <tr> <td>Operating Weight (kgs)</td> <td>3650</td> </tr> <tr> <td colspan="2"><b>3 Motor</b></td> </tr> <tr> <td>Type</td> <td>TEFC</td> </tr> <tr> <td>Volt/Phase/Hz</td> <td>380/3/50HZ</td> </tr> <tr> <td>Power</td> <td>5HP 3.7kw</td> </tr> <tr> <td colspan="2"><b>4 Fan</b></td> </tr> <tr> <td>Type</td> <td>Axial</td> </tr> <tr> <td>Diameter (mm)</td> <td>ø1800</td> </tr> <tr> <td>No. of Fan</td> <td>1</td> </tr> <tr> <td>Transmission Type</td> <td>Vee Belt</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>	<b>1 Design Condition</b>		Nominal Flow (m <sup>3</sup> /hr)	175.0	Water Out Temp.	32°C	Water In Temp.	37°C	Ambient Wet Bulb Temp.	28°C	<b>2 Overall Dimension</b>		Length (mm)	4400	Width (mm)	2300	Height (mm)	4430	Net Weight (kgs)	1525	Operating Weight (kgs)	3650	<b>3 Motor</b>		Type	TEFC	Volt/Phase/Hz	380/3/50HZ	Power	5HP 3.7kw	<b>4 Fan</b>		Type	Axial	Diameter (mm)	ø1800	No. of Fan	1	Transmission Type	Vee Belt									<table border="1"> <tr> <td><b>5 Material</b></td> <td></td> </tr> <tr> <td>Air Inlet Louver (Optional)</td> <td>FRP</td> </tr> <tr> <td>Basin</td> <td>FRP</td> </tr> <tr> <td>Bolt &amp; Nuts</td> <td>Electroplated</td> </tr> <tr> <td>Casing Panel</td> <td>FRP</td> </tr> <tr> <td>Distribution Tray</td> <td>FRP</td> </tr> <tr> <td>Eliminator</td> <td>FRP</td> </tr> <tr> <td>Fan Blade</td> <td>Al. Alloy or FRP</td> </tr> <tr> <td>Fan Hub</td> <td>GI + Al. Alloy</td> </tr> <tr> <td>Fan Guard</td> <td>Hot Dip Galv. Steel</td> </tr> <tr> <td>Fan Stack</td> <td>FRP</td> </tr> <tr> <td>Infill</td> <td>PVC</td> </tr> <tr> <td>Infill Support Mesh</td> <td>Hot Dip Galv. Steel</td> </tr> <tr> <td>Ladder</td> <td>Hot Dip Galv. Steel</td> </tr> <tr> <td>Motor Support</td> <td>Hot Dip Galv. Steel</td> </tr> <tr> <td>Strainer</td> <td>SS 304</td> </tr> <tr> <td>Structure</td> <td>Hot Dip Galv. Steel</td> </tr> <tr> <td>Sump Tank</td> <td>FRP</td> </tr> <tr> <td colspan="2"><b>6 Piping</b></td> </tr> <tr> <td>Inlet (Dia/Qty)</td> <td>ø125mm x 2</td> </tr> <tr> <td>Outlet (Dia/Qty)</td> <td>ø200mm x 1</td> </tr> <tr> <td>Overflow (Dia/Qty)</td> <td>ø65mm x 1</td> </tr> <tr> <td>Drain (Dia/Qty)</td> <td>ø65mm x 1</td> </tr> <tr> <td>Make-up (Dia/Qty)</td> <td>ø25mm x 1</td> </tr> <tr> <td>Manual Make-up (Dia/Qty)</td> <td>ø25mm x 1</td> </tr> <tr> <td>Suction tank</td> <td>1</td> </tr> </table>	<b>5 Material</b>		Air Inlet Louver (Optional)	FRP	Basin	FRP	Bolt & Nuts	Electroplated	Casing Panel	FRP	Distribution Tray	FRP	Eliminator	FRP	Fan Blade	Al. Alloy or FRP	Fan Hub	GI + Al. Alloy	Fan Guard	Hot Dip Galv. Steel	Fan Stack	FRP	Infill	PVC	Infill Support Mesh	Hot Dip Galv. Steel	Ladder	Hot Dip Galv. Steel	Motor Support	Hot Dip Galv. Steel	Strainer	SS 304	Structure	Hot Dip Galv. Steel	Sump Tank	FRP	<b>6 Piping</b>		Inlet (Dia/Qty)	ø125mm x 2	Outlet (Dia/Qty)	ø200mm x 1	Overflow (Dia/Qty)	ø65mm x 1	Drain (Dia/Qty)	ø65mm x 1	Make-up (Dia/Qty)	ø25mm x 1	Manual Make-up (Dia/Qty)	ø25mm x 1	Suction tank	1
<b>1 Design Condition</b>																																																																																																					
Nominal Flow (m <sup>3</sup> /hr)	175.0																																																																																																				
Water Out Temp.	32°C																																																																																																				
Water In Temp.	37°C																																																																																																				
Ambient Wet Bulb Temp.	28°C																																																																																																				
<b>2 Overall Dimension</b>																																																																																																					
Length (mm)	4400																																																																																																				
Width (mm)	2300																																																																																																				
Height (mm)	4430																																																																																																				
Net Weight (kgs)	1525																																																																																																				
Operating Weight (kgs)	3650																																																																																																				
<b>3 Motor</b>																																																																																																					
Type	TEFC																																																																																																				
Volt/Phase/Hz	380/3/50HZ																																																																																																				
Power	5HP 3.7kw																																																																																																				
<b>4 Fan</b>																																																																																																					
Type	Axial																																																																																																				
Diameter (mm)	ø1800																																																																																																				
No. of Fan	1																																																																																																				
Transmission Type	Vee Belt																																																																																																				
<b>5 Material</b>																																																																																																					
Air Inlet Louver (Optional)	FRP																																																																																																				
Basin	FRP																																																																																																				
Bolt & Nuts	Electroplated																																																																																																				
Casing Panel	FRP																																																																																																				
Distribution Tray	FRP																																																																																																				
Eliminator	FRP																																																																																																				
Fan Blade	Al. Alloy or FRP																																																																																																				
Fan Hub	GI + Al. Alloy																																																																																																				
Fan Guard	Hot Dip Galv. Steel																																																																																																				
Fan Stack	FRP																																																																																																				
Infill	PVC																																																																																																				
Infill Support Mesh	Hot Dip Galv. Steel																																																																																																				
Ladder	Hot Dip Galv. Steel																																																																																																				
Motor Support	Hot Dip Galv. Steel																																																																																																				
Strainer	SS 304																																																																																																				
Structure	Hot Dip Galv. Steel																																																																																																				
Sump Tank	FRP																																																																																																				
<b>6 Piping</b>																																																																																																					
Inlet (Dia/Qty)	ø125mm x 2																																																																																																				
Outlet (Dia/Qty)	ø200mm x 1																																																																																																				
Overflow (Dia/Qty)	ø65mm x 1																																																																																																				
Drain (Dia/Qty)	ø65mm x 1																																																																																																				
Make-up (Dia/Qty)	ø25mm x 1																																																																																																				
Manual Make-up (Dia/Qty)	ø25mm x 1																																																																																																				
Suction tank	1																																																																																																				